



ERDWICH

... SHREDDING UNLIMITED ...

ERDWICH
SWARF-SHREDDING-DRUM
TSZ 1500
TSZ 1500S



Advantages and special features

ERDWICH swarf-shredding-drum TSZ 1500(S)

■ Flexibel:

- | Ideal solution at smaller and middle swarf quantities
- | Feeding with different swarf containers is no problem

■ Optimum material feeding:

- | Rotating drum enables a continual and constant feeding of swarf to the cutting unit

■ Absolute process reliability:

- | Single-shaft shredding technology with double ejection flap (TSZ 1500S) for extraneous material provides for smooth system operation.

■ Safe separation of extraneous material:

- | Automatic separation from material stream into containers for extraneous material, as well as discharge of swarf in the swarf conveyor below

■ Efficient and secure working:

- | Via smart SPS system control with automatic recognition of massive parts – with reverse operation for protection of machine

■ Simple maintenance:

- | By extricable cutting unit with single-stuck, detachable knife blades at the cutting rotor



ERDWICH

... SHREDDING UNLIMITED ...

ERDWICH
SWARF-SHREDDING-DRUM
TSZ 1500
TSZ 1500S



Technical Data

Type	Number of shafts	Drive power in kW	Rotor length / diameter (mm)	Weight kg	Blades thickness* mm
TSZ 1500	1	9,2	575 x Ø 242	1.380	25
TSZ 1500S	1	5,5	575 x Ø 242	1.590	25

Dimensions		
	Dimension	TSZ 1500(S)
Total length C	mm	2.000
Total height A	mm	2.620
Total width B	mm	2.275
Drum diameter D	mm	1.500
Drum height E	mm	1.300
Max. drum-filling level	litre	1.200
Minimum building inside height F	mm	4.200

Subject to technical changes.

*Standard version

